



D5496-1 CONNECTOR

RELEASED
2019 AUG 06 NO
ECN19-804

NOTES:

- 1) MATERIAL: 6061-T6/T62/T651 ALUMINUM SHEET OR PLATE, 0.250" THK
PER QQ-A-250/11 OR AMS-QQ-A-250/11
OR AMS 4025 OR AMS 4027
OR ASTM B209
REF DART SPEC M6061T6S0.250
- 2) FINISH: ANODIZE BLACK PER MIL-A-8625F TYPE I OR IB OR IC OR II OR IIB CLASS 2
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.010 TO 0.030 MAX
- 6) IDENTIFICATION: PER DART QSI 044 6.1
- 7) WEIGHT: 0.13 lbs

D	REVISED NOTE 2 TO ANODIZE FINISH AND REMOVED NOTE 8 (ZN A8-1)	RF	19.07.16
C	REVISED HOLE LOCATION, REMOVED TOP LUG, REDUCED THICKNESS TO 0.230 AROUND ATTACHMENT HOLES	RF	18.10.17
B	REMOVED -041; REVISED NOTES; REVISED CENTER HOLE; REVISED PART HEIGHT (ZN D6-1)	VS	18.05.23
A	NEW ISSUE	VS	18.02.27
REV.	DESCRIPTION	BY	DATE
DESIGN	VS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	SAD	DRAWING NO.	REV. D
MFG. APPR.	DD	D5496	SHEET 1 OF 1
APPROVED	VS	TITLE	SCALE
DE APPR.	DS	CONNECTOR	NTS
DATE	19.07.16	COPYRIGHT © 2018 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

APPROVED